



SMEC INTERNAL REF. C1917

Traffic Impact Assessment

Proposed Heather Park Development

Reference No. C1917

Prepared for Urban Front Developers

15 November 2022

Document Control

Document	Traffic Impact Assessment
File Location	P:\C1917_TIA Erf 19734 Heather Park\3_Working\3-4_DivT\Reports
Project Name	Proposed Heather Park Development
Project Number	C1917

Revision History

Revision No.	Date	Prepared By	Reviewed By	Approved for Issue By
Draft for Review	10 June 2022	M Holmes JP Snyman	EB Jordaan, IntPE	EB Jordaan, IntPE
1	15 November 2022	M Holmes	EB Jordaan, IntPE	EB Jordaan, IntPE

Issue Register

Distribution List	Date Issued	Number of Copies
Urban Front Developers	15 November 2022	1 - PDF

SMEC Company Details

Approved by	EB Jordaan, IntPE		
Address	13 Progress Street, Dormehlsdrift, George, 6529		
Telephone	+27 44 873 5029	Facsimile	
Email	emile.jordaan@smec.com	Website	www.smec.com
Signature			

The information within this document is and shall remain the property of: SMEC South Africa (Pty) Ltd - George

Important Notice

This report is confidential and is provided solely for the purposes of the Traffic Impact Assessment for the Proposed Heather Park Development, George. This report is provided pursuant to a Consultancy Agreement between SMEC South Africa Pty Limited ("SMEC") and Urban Front Developers, under which SMEC undertook to perform a specific and limited task for Urban Front Developers. This report is strictly limited to the matters stated in it and subject to the various assumptions, qualifications and limitations in it and does not apply by implication to other matters. SMEC makes no representation that the scope, assumptions, qualifications and exclusions set out in this report will be suitable or sufficient for other purposes nor that the content of the report covers all matters which you may regard as material for your purposes.

This report must be read as a whole. Any subsequent report must be read in conjunction with this report.

The report supersedes all previous draft or interim reports, whether written or presented orally, before the date of this report. This report has not and will not be updated for events or transactions occurring after the date of the report or any other matters which might have a material effect on its contents, or which come to light after the date of the report. SMEC is not obliged to inform you of any such event, transaction or matter nor to update the report for anything that occurs, or of which SMEC becomes aware, after the date of this report.

Unless expressly agreed otherwise in writing, SMEC does not accept a duty of care or any other legal responsibility whatsoever in relation to this report, or any related enquiries, advice or other work, nor does SMEC make any representation in connection with this report, to any person other than Urban Front Developers. Any other person who receives a draft or a copy of this report (or any part of it) or discusses it (or any part of it) or any related matter with SMEC, does so on the basis that he or she acknowledges and accepts that he or she may not rely on this report nor on any related information or advice given by SMEC for any purpose whatsoever.

Table of Contents

1	Introduction.....	1
2	Background Information	3
2.1	Existing Roads	3
2.2	Arterial Management Plan	4
2.2.1	Road Classification.....	4
2.2.2	Land Use	5
2.3	Public Transport Facilities	5
2.4	Non-Motorized Transport Facilities.....	5
2.5	Site Access	6
2.6	Access Spacing Requirements.....	7
3	Other Planning Authorities	7
4	Traffic Demand Estimation	7
4.1	Assessment Years.....	7
4.2	Assessment Hours	7
4.3	Traffic Counts.....	7
4.4	Traffic Growth Rates.....	9
5	Trip Generation and Distribution.....	11
5.1	Trip Generation.....	11
5.2	Trip Distribution.....	11
5.3	Traffic Assignment.....	11
6	Traffic Analysis	15
6.1	National Route 9 and Plantation Road.....	16
6.2	National Route 9 and Witfontein Road	17
6.3	Analysis Summary	18
7	Site Impact Assessment	19
7.1	Internal Operations.....	19
7.2	Parking	19
7.3	Loading	19
7.4	Throat Length.....	19
8	Proposed Capacity Improvements.....	20
9	Conclusion and Recommendations	21

Annexures

Annexure A	Site Development Plan.....	22
Annexure B	Traffic Survey Data	24
Annexure C	Detailed SIDRA Outputs.....	32

List of Tables

Table 4-1: Typical Growth Rates.....	9
Table 5-1: Trip Generation.....	11
Table 6-1: Intersection-Based Level of Service Criteria	15
Table 6-2: Analysis Summary.....	18

List of Figures

Figure 1-1: Locality Plan (Source: OpenStreetMap).....	1
Figure 1-2: Site Development Plan (Source: Urban Front Developers – November 2022).....	2
Figure 2-1: Existing Roads	3
Figure 2-2: Proposed Road Upgrades to Witfontein Road.....	4
Figure 2-3: Existing GIPTN Routes (George LM)	5
Figure 2-4: Planned NMT Infrastructure Projects (Iliso).....	6
Figure 2-5: Proposed Site Access and Access Spacing	6
Figure 4-1: Traffic Count Locations	8
Figure 4-2: 2022 Base Year Traffic Flows.....	9
Figure 4-3: 2027 Forecast Year traffic flows.....	10
Figure 5-1: Trip Distribution (New Trips)	12
Figure 5-2: Traffic Assignment (New Trips).....	13
Figure 5-3: 2027 Base + Development Trips	14
Figure 6-1: National Route 9 (C J Langenhoven Road) and Plantation Road: Existing Layout.....	16
Figure 6-2: National Route 9 (C J Langenhoven Road) and Witfontein Road: Existing Layout.....	17

1 Introduction

SMEC South Africa (Pty) Ltd was appointed by Urban Front Developers to conduct a Traffic Impact Assessment for the proposed Heather Park residential development on Erf 19734, George. The site is bounded by Plantation Road to the east and Homewood Street to the south. A locality plan is shown in **Figure 1-1**.




Figure 1-1: Locality Plan (Source: OpenStreetMap)

The site measures approximately 5,6 Hectares in extent and will comprise of 77 townhouses (simplexes and duplexes) and 40 Flats. An extract of the proposed Site Development Plan is shown in **Figure 1-2**. Refer to **Annexure A** for the full Site Development Plan.

The purpose of the Traffic Impact Assessment is to quantify the anticipated impact of the development traffic, and recommend remedial measures as required. The study was conducted in accordance with The Committee of Transport Officials South African Traffic Impact and Site Traffic Assessment Manual (COTO, TMH 16 Volume 1).



Figure 1-2: Site Development Plan (Source: Urban Front Developers – November 2022)

2 Background Information

2.1 Existing Roads

National Route 9 (C J Langenhoven Road) is classified as a Class 2 Major Arterial within the George Roads Masterplan. In the vicinity of the site, it comprises of one lane per direction. It experiences moderate traffic flows during peak hours.

Witfontein Road is classified as Class 3 Minor Arterial within the George Roads Masterplan. In the vicinity of the site, it comprises of one lane per direction. It experiences moderate traffic flows during peak hours.

Plantation Road is a Class 4 Collector Road, serving the surrounding residential area. The road comprises of one lane per direction in the vicinity of the subject site. It experiences low traffic flows during peak hours

Homewood Street is classified as a Class 5 Local Street, serving the surrounding residential area. The road comprises of one lane per direction, and experiences low traffic flows during peak hours.

Refer to **Figure 2-1**.



Figure 2-1: Existing Roads

2.2 Arterial Management Plan

An Arterial Management Plan (AMP) was undertaken for both the George/Witfontein Corridor and CJ Langenhoven Road by V3 Consulting Engineers (Pty) Ltd and published as follows:

- George/Witfontein Corridor Final Draft (November 2019).
- CJ Langenhoven Road Final Draft (Rev 1) (April 2020).

2.2.1 Road Classification

2.2.1.1 George/Witfontein Corridor

The AMP states that Witfontein Street has been classified as a Class 3 Minor Arterial within a Suburban Roadside Environment. Status Quo intersection spacings were reportedly non-compliant with a Suburban Roadside Environment and recommendations were made to better comply with the Western Cape Government Access Management Guidelines. Refer to **Figure 2-2**.



Figure 2-2: Proposed Road Upgrades to Witfontein Road

2.2.1.2 CJ Langenhoven Road

The AMP confirms that CJ Langenhoven Road is classified as a Class 2 Major Arterial in the vicinity of the site. Roadside development environment was defined as suburban in the vicinity of Plantation Road.

It was highlighted that the existing spacing (approx. 168 m) of Plantation Road intersection and Morning Glory Lane along C J Langenhoven is sub-standard. In accordance with WCG Access Management Guidelines (2020) the required spacing from an unsignalised full intersection to an unsignalised full intersection along a Class 2 road in a suburban roadside development environment is 270 m. No remedial measures, however, were proposed.

2.2.2 Land Use

2.2.2.1 George/Witfontein Corridor

The land use along Witfontein Road is mainly focused around low to medium density residential development, with a section of commercial and retail development within approximately 160m of CJ Langenhoven Street. The existing built fabric along Witfontein Road consists mainly of a range of building types, varying from single- to medium density residential dwellings, to retail and commercial developments.

No densification is proposed along the Witfontein Road yet the Municipal Spatial Development Framework identifies the commercial and retail development node as the Heather Park TOD node.

2.2.2.2 CJ Langenhoven Road

The land use along CJ Langenhoven in the vicinity of Plantation Road is predominantly residential in character and no significant increase of densification was reported.

2.3 Public Transport Facilities

Heather Park is served by the existing Go George service, with routes running along Witfontein Road onto George Road, linking the local workforce with employment opportunities. The existing GIPTN is shown in **Figure 2-3**.




Figure 2-3: Existing GIPTN Routes (George LM)

2.4 Non-Motorized Transport Facilities

The George CIP (Iliso 2014/15) provides a snapshot of the existing NMT network within George. There are no formal pedestrian walkways along of Plantation Road in the vicinity of the proposed development, however, a formal pedestrian walkway is provided along the south edge of CJ Langenhoven Street in the vicinity of the development. The planned NMT Network is shown in **Figure 2-4**.




Figure 2-4: Planned NMT Infrastructure Projects (Iliso)

2.5 Site Access

The subject site is proposed to be served by one access at the end of Plantation Road. Refer to **Figure 2-5**.



Figure 2-5: Proposed Site Access and Access Spacing

Consideration was given to providing site access via the northward extension of Homewood Street however this was later disregarded due to the following:

1. Opposition to additional vehicular trips along the street by local homeowners.
2. Existing sub-standard spacing along Witfontein Road.

2.6 Access Spacing Requirements

The access spacing requirements were derived from the Western Cape Government (WCG) Access Management Guidelines (2020).

The minimum spacing of an unsignalised full intersection along a Class 2 Road within a suburban roadside environment, upstream or downstream of an unsignalised full intersection is 270 metres.

It is confirmed that Plantation Road conforms to the WCG access spacing requirements to the north. However, as identified in the C J Langenhoven Road AMP, spacing to the southern intersection with Morning Glory Lane does not conform to the WCG access spacing requirements.

3 Other Planning Authorities

C J Langenhoven Road falls under the jurisdiction of the Western Cape Department of Transport. As such, they would need to be included in the approval process.

4 Traffic Demand Estimation

4.1 Assessment Years

A base year assessment was undertaken to identify shortcomings in the road-based capacity in the short term, if any. In addition thereto, it is required to grow traffic flows to an acceptable horizon year in order to ensure that the proposed road network would be able to operate satisfactorily once the development traffic is added to the surrounding road network.

TMH 16 Volume 1 Version 1.0, states that transportation improvements for developments must be designed for a horizon year of 5 years. Hence, a 2022 Base Year and a 2027 Design Year was used for this TIA.

4.2 Assessment Hours

The assessment has been undertaken considering the periods during which the combined effect of background and development traffic would result in the highest traffic demand. Hence, it was deemed suitable to assess the Weekday AM and PM Peak Hours.

4.3 Traffic Counts

Taking into consideration the location and extent of the proposed development with relation to the surrounding road network, the following traffic count surveys were undertaken as part of this project assignment:

- Counting Station 1: Intersection of the N9 (C J Langenhoven Road) and Plantation Road;
- Counting Station 2: Intersection of the N9 (C J Langenhoven Road) and Witfontein Road; and

Traffic count locations are shown in **Figure 4-1**.




Figure 4-1: Traffic Count Locations

Details of the traffic survey are provided below:

- Date counted; 12 May 2022
- Day; Normal Weekday
- Congestion levels; Low
- Enumerator; SMEC South Africa (Pty) Ltd

The detailed traffic survey data is provided in **Annexure B**.

A common peak hour was identified for the intersections under discussion, as follows:

- Weekday AM Peak Hour 07h00 – 08h00
- Weekday AM Peak Hour 16h30 – 17h30

The 2022 Base Year traffic flows are shown in **Figure 4-2**.




Figure 4-2: 2022 Base Year Traffic Flows

4.4 Traffic Growth Rates

A traffic growth rate is applied to background traffic in order to determine the anticipated growth in this traffic besides that relating to planned and new developments. The Committee of Transport Officials Trip Data Manual (COTO, TMH 17 Volume 1 Version 1.01) provides typical growth rates to be used for growth areas based on the existing/anticipated rate of growth. Refer to **Table 4-1**.

Table 4-1: Typical Growth Rates

Development Area	Growth Rate
Low Growth Areas	0% - 3%
Average Growth Areas	3% - 4%
Above Average Growth Areas	4% - 6%
Fast Growing Areas	6% - 8%
Exceptionally High Growth Areas	> 8%

Taking into consideration the nature and extent of development within this area, an annual compounded traffic growth rate of 3.0% was applied to the 2022 background through traffic along Witfontein Road and CJ Langehoven Road in order to derive the 2027 Design Year traffic flows.

The 2027 Forecast Year traffic flows are shown in **Figure 4-3**.




Figure 4-3: 2027 Forecast Year traffic flows

5 Trip Generation and Distribution

5.1 Trip Generation

The Trip Generation Rates for the land use types forming part of the development were obtained from the COTO TMH 17 South African Trip Data Manual dated September 2012.

The trip generation potential of the development is shown in **Table 5-1**.

Table 5-1: Trip Generation

Land Use	Units	Trip Generation Rates (per Unit)		Adjustment Factor	Traffic generation (vph)			
		Weekday			Weekday			
					AM		PM	
		AM	PM		IN	OUT	IN	OUT
Apartments and Flats	40	0.65	0.65	1.00	7	20	19	8
Townhouses (Simplexes and Duplexes)	77	0.85	0.85	1.00	17	50	46	20
Total New Trips					24	70	65	28
					94		93	

It is anticipated that the development would generate 94 and 93 new vehicular trips during the Weekday AM and PM Peak Hours respectively.

5.2 Trip Distribution

Trip distribution was estimated manually, based on existing traffic flows, the land use of the surrounding areas and the proposed access configuration. Refer to **Figure 5-1**.

5.3 Traffic Assignment

Traffic assignment involves determining the amount of traffic that will use specific routes in the network. The traffic assignment is made with consideration to logical routings, available roadway capacity, right-turn movements, travel times and other factors. Refer to **Figure 5-2**.

The 2027 Base + Development Trips are shown in **Figure 5-3**.




Figure 5-1: Trip Distribution (New Trips)




Figure 5-2: Traffic Assignment (New Trips)




Figure 5-3: 2027 Base + Development Trips

6 Traffic Analysis

Intersection capacity analyses were undertaken to determine the anticipated operational performance of the site access and surrounding road network, taking into consideration the implementation of the development and associated development trips. The state-of-the-art traffic engineering software package, SIDRA Intersection 8.0 software, was used. The intersections analysed for the development are listed below:

- National Route 9 (C J Langenhoven Road) and Plantation Road;
- National Route 9 (C J Langenhoven Road) and Witfontein Road; and

The following scenarios were analysed as part of this project assignment:

- 2022 Background Traffic; and
- 2027 Background + Development Traffic.

The operational performance of an intersection is typically quantified in terms of Level of Service as defined by the SIDRA Intersection User Guide Ver. 8 (2018). These definitions relate average delays at intersections (for individual turning movements, for each approach and for the overall intersection) to a level of service ranging from A to F, as are shown in **Table 6-1**.

Table 6-1: Intersection-Based Level of Service Criteria

Level of Service	Control Delay per Vehicle in Seconds (d)			LOS for V/C Ratio
	Signals and	Roundabouts	Stop Signs and Yield Signs	V/C > 1
A	$d \leq 10$	$d \leq 10$	$d \leq 10$	F
B	$10 < d \leq 20$	$10 < d \leq 20$	$10 < d \leq 15$	F
C	$20 < d \leq 35$	$20 < d \leq 35$	$15 < d \leq 25$	F
D	$35 < d \leq 55$	$35 < d \leq 50$	$25 < d \leq 35$	F
E	$55 < d \leq 80$	$50 < d \leq 70$	$35 < d \leq 50$	F
F	$80 < d$	$70 < d$	$50 < d$	F

Detailed SIDRA outputs are contained in **Annexure C**.

6.1 National Route 9 and Plantation Road

The existing intersection of National Route 9 (C J Langenhoven Road) and Plantation Road is a priority-controlled intersection with stop control along the east and west approaches. The north approach comprises of a shared through-and-left lane and a short right-turn lane. The east approach comprises a short left-turn lane and shared through-and-right-turn lane. The south approach comprises of a shared through-and-left lane and a short right-turn lane. The west approach comprises of a single lane serving all directions. Refer to **Figure 6-1**.




Figure 6-1: National Route 9 (C J Langenhoven Road) and Plantation Road: Existing Layout

2022 Background Traffic

Taking into consideration the 2022 Base Year traffic flows, the worst stop-control approach operates at Level of Service A during both the Weekday AM and PM Peak Hours, with an average delay of approximately 9 seconds for both peak hours.

It is concluded that the existing intersection configuration is able to accommodate the 2022 Background Traffic at an acceptable Level of Service.

2027 Background + Development Traffic

Taking into consideration the 2027 Background Traffic plus the anticipated development traffic flows, the worst stop-control approach will operate at Level of Service A during both the Weekday AM and PM Peak Hours, with an average delay of approximately 9 and 10 seconds respectively.

It is concluded that the existing intersection configuration would be able to accommodate the 2027 Background + Development Traffic at an acceptable Level of Service.

6.2 National Route 9 and Witfontein Road

The existing intersection of National Route 9 (C J Langenhoven Road) and Witfontein Road is a priority-controlled roundabout. The north approach comprises of a short shared through-and-left lane and a through and right-turn lane. The east approach comprises a short left-turn lane and shared through-and-right-turn lane. The south approach comprises of a short left-turn slip-lane and a single lane serving all directions. The west approach comprises of a right-turn lane and a single lane serving all directions. Refer to **Figure 6-2**.




Figure 6-2: National Route 9 (C J Langenhoven Road) and Witfontein Road: Existing Layout

2022 Background Traffic

Taking into consideration the 2022 Base Year traffic flows, the intersection operates at Level of Service A during both the Weekday AM and PM Peak Hours, with an average delay of approximately 7 and 6 seconds respectively.

It is concluded that the existing intersection configuration is able to accommodate the 2022 Background Traffic at an acceptable Level of Service.

2027 Background + Development Traffic

Taking into consideration the 2027 Background Traffic plus the anticipated development traffic flows, the intersection will operate at Level of Service A during both the Weekday AM and PM Peak Hours, with an average delay of approximately 7 and 6 seconds respectively.

It is concluded that the existing intersection configuration would be able to accommodate the 2027 Background + Development Traffic at an acceptable Level of Service.

6.3 Analysis Summary

A summary of the analysis outputs is provided in **Table 6-2**.

Table 6-2: Analysis Summary

Intersection	2022 Base Year		2027 Background + Development	
	AM	PM	AM	PM
National Route 9 and Plantation Road	A	A	A	A
National Route 9 and Witfontein Road	A	A	A	A

7 Site Impact Assessment

7.1 Internal Operations

Provision should be made for an ease of circulation as part of the internal layout of the planned development.

7.2 Parking

Parking provision is an important consideration of any development and would ultimately ensure that vehicular traffic is accommodated on-site in its entirety. Insufficient parking provision would have dire consequences on the operational performance of the site and surrounding public roads, as well as on road safety.

The George Zoning Scheme By-Law (2016) was used to ascertain the parking standards to be adhered to, based on the site-specific land use rights for the development area.

A minimum of 2 parking bays per dwelling unit plus 0.25 parking bays per dwelling unit for visitors is required for Townhouses (Simplexes and Duplexes), thus totalling 174 parking bays.

A minimum of 1.75 parking bays per dwelling plus 0.25 parking bays per dwelling for visitors is required for flats, thus totalling 80 parking bays.

Therefore, the total development would need to accommodate 254 parking bays.

4 parking bays are to be accessible to the physically disabled.

7.3 Loading

Loading bays are not stipulated as a requirement for residential land uses in the George Zoning Scheme By-Law (2016). However, the Municipality may determine off-street loading requirements for uses not stipulated in the by-law on a case-by-case basis.

7.4 Throat Length

Adequate throat length provision is essential in ensuring sufficient operation of a development access and preventing possible spill-back onto the surrounding public road.

A throat length of 46 m (measured from the access control location to the development boundary) has been provided on the Site Development Plan.

It is our submission that the throat length provided would be sufficient to accommodate the anticipated traffic demand.

It is however recommended that visitors bays are not provided within the throat leading to the development access, as is currently shown on the Site Development Plan.

8 Proposed Capacity Improvements

No capacity improvements are proposed as part of the planned development.

9 Conclusion and Recommendations

SMEC South Africa (Pty) Ltd was appointed by Urban Front Developers to conduct a Traffic Impact Assessment for the proposed Heather Park residential development on Erf 19734, George. The site measures approximately 5,6 Hectares in extent and will comprise of 77 townhouses (simplexes and duplexes) and 40 flats.

The subject site is proposed to be served by a single access on Plantation Road.


It is anticipated that the development would generate 94 and 93 new vehicular trips during the Weekday AM and PM Peak Hours, respectively.

Following our assessment, it is evident that no capacity improvements are required as part of the planned development. Existing intersection layouts are capable of serving the anticipated new development trips.

It is however recommended that visitors bays are not provided within the throat leading to the development access, as is currently shown on the Site Development Plan.

This development is supported from a traffic engineering perspective.

Annexure A Site Development Plan



Annexure B Traffic Survey Data

Counting Station 1: Intersection of the N9 and Plantation Road



Verkeerstelling/Traffic Count

Projek Nr/Projek Name

Plek/Location: GEORGIE - SCARCO : PLANTASIE / N12

Datum/Date: 12 Mei 2022

Teller/Counter: N12

N2 N2 N2

Tyd	1				2				3			
	LIGHT	HEAVY	MBT	BUS	LIGHT	HEAVY	MBT	BUS	LIGHT	HEAVY	MBT	BUS
05:45 - 06:00												
06:00 - 06:15	0	0	0	0	3	0	1	0	0	0	0	0
06:15 - 06:30	0	0	0	0	17	6	2	0	0	0	0	0
06:30 - 06:45	1	0	0	0	37	8	3	0	1	0	0	0
06:45 - 07:00	1	0	0	0	59	10	3	0	1	0	0	0
07:00 - 07:15	2	0	0	0	80	15	3	0	1	0	0	0
07:15 - 07:30	2	0	0	0	109	19	6	0	2	0	0	0
07:30 - 07:45	2	0	0	0	133	21	8	0	2	0	0	0
07:45 - 08:00	2	0	0	0	169	27	8	0	2	0	0	0
08:00 - 08:15	3	0	0	0	206	33	8	0	2	0	0	0
08:15 - 08:30	4	0	0	0	247	38	8	0	2	0	0	0
08:30 - 08:45	4	0	0	0	302	47	8	0	2	0	0	0
08:45 - 09:00	4	0	0	0	345	52	8	0	2	0	0	0
09:00 - 09:15												
14:45 - 15:00												
15:00 - 15:15	1	0	0	0	3	6	1	0	1	0	0	0
15:15 - 15:30	2	0	0	0	83	13	1	0	1	0	0	0
15:30 - 15:45	4	0	0	0	103	15	2	0	1	0	0	0
15:45 - 16:00	9	0	0	0	131	16	2	0	3	0	0	0
16:00 - 16:15	11	0	0	0	176	19	4	0	3	0	0	0
16:15 - 16:30	15	0	0	0	216	23	4	0	3	0	0	0
16:30 - 16:45	17	0	0	0	251	24	6	0	4	0	0	0
16:45 - 17:00	20	0	0	0	296	24	7	0	5	0	0	0
17:00 - 17:15	21	0	0	0	343	28	7	0	5	0	0	0
17:15 - 17:30	22	0	0	0	394	33	8	0	6	0	0	0
17:30 - 17:45	24	0	0	0	423	36	8	0	7	0	0	0
17:45 - 18:00	25	0	0	0	445	38	9	0	8	0	0	0
18:00 - 18:15												



Verkeerstelling/Traffic Count

Projek Nr/Projek Name _____

Plek/Location: _____

Datum/Date: _____

Teller/Counter: _____

PLANTASIE WEG

PLANTASIE WEG

PLANTASIE WEG

Tyd	4				5				6.			
	LIGHT	HEAVY	MBT	BUS	LIGHT	HEAVY	MBT	BUS	LIGHT	HEAVY	MBT	BUS
05:45 - 06:00												
06:00 - 06:15	0	0	0	0	0	0	0	0	0	0	0	0
06:15 - 06:30	0	0	0	0	0	0	0	0	0	0	0	0
06:30 - 06:45	0	0	0	0	0	0	0	0	0	0	0	0
06:45 - 07:00	0	0	0	0	0	0	0	0	0	0	0	0
07:00 - 07:15	0	0	0	0	0	0	0	0	0	0	0	0
07:15 - 07:30	0	0	0	0	0	0	0	0	0	0	0	0
07:30 - 07:45	0	0	0	0	0	0	0	0	0	0	0	0
07:45 - 08:00	0	0	0	0	0	0	0	0	0	0	0	0
08:00 - 08:15	0	0	0	0	0	0	0	0	0	0	0	0
08:15 - 08:30	0	0	0	0	0	0	0	0	0	0	0	0
08:30 - 08:45	0	0	0	0	0	0	0	0	0	0	0	0
08:45 - 09:00	2	0	0	0	0	0	0	0	0	0	0	0
09:00 - 09:15												
14:45 - 15:00												
15:00 - 15:15	3	0	0	0	0	0	0	0	0	0	0	0
15:15 - 15:30	3	0	0	0	0	0	0	0	0	0	0	0
15:30 - 15:45	3	0	0	0	0	0	0	0	0	0	0	0
15:45 - 16:00	3	0	0	0	0	0	0	0	0	0	0	0
16:00 - 16:15	3	0	0	0	0	0	0	0	0	0	0	0
16:15 - 16:30	3	0	0	0	0	0	0	0	0	0	0	0
16:30 - 16:45	3	0	0	0	0	0	0	0	0	0	0	0
16:45 - 17:00	5	0	0	0	0	0	0	0	0	0	0	0
17:00 - 17:15	7	0	0	0	0	0	0	0	0	0	0	0
17:15 - 17:30	7	0	0	0	0	0	0	0	0	0	0	0
17:30 - 17:45	7	0	0	0	0	0	0	0	1	0	0	0
17:45 - 18:00	9	0	0	0	0	0	0	0	2	0	0	0
18:00 - 18:15												



Verkeerstelling/Traffic Count

Projek Nri/Projek Name _____

Plek/Location: _____

Datum/Date: _____

Teller/Counter: _____

N12

N12

N12

Tyd	7				8				9			
	LIGHT	HEAVY	MBT	BUS	LIGHT	HEAVY	MBT	BUS	LIGHT	HEAVY	MBT	BUS
05:45 - 06:00												
06:00 - 06:15	0	0	0	0	3	0	3	0	0	0	0	0
06:15 - 06:30	0	0	0	0	16	1	5	1	0	0	0	0
06:30 - 06:45	0	0	0	0	44	2	7	1	0	0	0	0
06:45 - 07:00	0	0	0	0	82	2	8	1	0	0	0	0
07:00 - 07:15	0	0	0	0	128	3	8	1	0	0	0	0
07:15 - 07:30	0	0	0	0	163	5	8	1	0	0	0	0
07:30 - 07:45	0	0	0	0	178	7	8	1	0	0	0	0
07:45 - 08:00	0	0	0	0	204	8	8	1	0	0	0	0
08:00 - 08:15	0	0	0	0	229	9	8	1	0	0	0	0
08:15 - 08:30	0	0	0	0	262	10	8	1	0	0	0	0
08:30 - 08:45	0	0	0	0	283	11	9	2	0	0	0	0
08:45 - 09:00	0	0	0	0	314	15	9	3	0	0	0	0
09:00 - 09:15												
14:45 - 15:00												
15:00 - 15:15	0	0	0	0	40	1	0	0	0	0	0	0
15:15 - 15:30	0	0	0	0	72	7	0	0	0	0	0	0
15:30 - 15:45	0	0	0	0	100	15	0	0	0	0	0	0
15:45 - 16:00	0	0	0	0	149	17	0	0	0	0	0	0
16:00 - 16:15	0	0	0	0	188	23	0	0	0	0	0	0
16:15 - 16:30	0	0	0	0	239	28	0	0	0	0	0	0
16:30 - 16:45	0	0	0	0	272	32	0	0	0	0	0	0
16:45 - 17:00	0	0	0	0	309	35	0	0	0	0	0	0
17:00 - 17:15	0	0	0	0	348	39	0	1	0	0	0	0
17:15 - 17:30	0	0	0	0	381	42	1	1	0	0	0	0
17:30 - 17:45	0	0	0	0	415	42	1	1	0	0	0	0
17:45 - 18:00	0	0	0	0	442	48	6	1	0	0	0	0
18:00 - 18:15												



Verkeerstelling/Traffic Count

Projek Nri/Projek Name _____

Plek/Location: _____

Datum/Date: _____

Teller/Counter: _____

Tyd	10				11				12			
	PLANTAGIE		WEG		PLANTAGIE		WEG		PLANTAGIE		WEG	
	LIGHT	HEAVY	MBT	BUS	LIGHT	HEAVY	MBT	BUS	LIGHT	HEAVY	MBT	BUS
05:45 - 06:00												
06:00 - 06:15	0	0	0	0	0	0	0	0	0	0	0	0
06:15 - 06:30	0	0	0	0	0	0	0	0	1	0	0	0
06:30 - 06:45	0	0	0	0	0	0	0	0	3	0	0	0
06:45 - 07:00	0	0	0	0	0	0	0	0	7	0	0	0
07:00 - 07:15	0	0	0	0	0	0	0	0	10	0	0	0
07:15 - 07:30	0	0	0	0	0	0	0	0	11	0	0	0
07:30 - 07:45	0	0	0	0	0	0	0	0	13	0	0	0
07:45 - 08:00	0	0	0	0	0	0	0	0	14	0	0	0
08:00 - 08:15	0	0	0	0	0	0	0	0	15	0	0	0
08:15 - 08:30	0	0	0	0	0	0	0	0	16	0	0	0
08:30 - 08:45	0	0	0	0	0	0	0	0	16	0	0	0
08:45 - 09:00	0	0	0	0	0	0	0	0	17	0	0	0
09:00 - 09:15												
14:45 - 15:00												
15:00 - 15:15	0	0	0	0	0	0	0	0	7	0	0	0
15:15 - 15:30	0	0	0	0	0	0	0	0	7	0	0	0
15:30 - 15:45	0	0	0	0	0	0	0	0	8	0	0	0
15:45 - 16:00	0	0	0	0	0	0	0	0	9	0	0	0
16:00 - 16:15	0	0	0	0	0	0	0	0	11	0	0	0
16:15 - 16:30	0	0	0	0	0	0	0	0	12	0	0	0
16:30 - 16:45	0	0	0	0	0	0	0	0	14	0	0	0
16:45 - 17:00	0	0	0	0	0	0	0	0	16	0	0	0
17:00 - 17:15	0	0	0	0	0	0	0	0	18	0	0	0
17:15 - 17:30	0	0	0	0	0	0	0	0	18	0	0	0
17:30 - 17:45	0	0	0	0	0	0	0	0	20	0	0	0
17:45 - 18:00	0	0	0	0	0	0	0	0	20	0	0	0
18:00 - 18:15												

Counting Station 2: Intersection of the N9 and Witfontein Road



Verkeerstelling/Traffic Count

Plek/Location:

GEORGE: (BLANCO) - SIRKEL (ENGEN/HEATHERPARK)

Datum/Date:

12:05:2022

Teller/Counter:

J.E. GIENELAR

N12

N12

N12

Tyd	1				2				3			
	LIGHT	HEAVY	MBT	BUS	LIGHT	HEAVY	MBT	BUS	LIGHT	HEAVY	MBT	BUS
05:45 - 06:00												
06:00 - 06:15	22	0	0	1	11	1	0	0	2	0	0	0
06:15 - 06:30	47	0	0	2	23	5	0	1	11	0	0	0
06:30 - 06:45	85	0	1	4	39	6	0	1	17	0	0	0
06:45 - 07:00	146	2	1	5	55	8	0	1	25	0	0	0
07:00 - 07:15	238	3	2	7	70	13	0	1	29	0	0	0
07:15 - 07:30	372	3	2	8	86	17	4	1	33	0	0	0
07:30 - 07:45	504	4	6	10	105	18	6	1	40	0	0	0
07:45 - 08:00	646	7	7	15	129	22	6	1	48	0	0	0
08:00 - 08:15	764	9	10	16	155	25	6	1	52	0	0	0
08:15 - 08:30	850	13	11	17	182	28	6	1	61	1	0	0
08:30 - 08:45	930	13	11	18	217	30	6	1	68	1	0	0
08:45 - 09:00	1014	16	11	19	240	33	6	1	78	1	0	0
09:00 - 09:15												
14:45 - 15:00												
15:00 - 15:15	128	1	0	4	20	2	0	0	10	0	0	0
15:15 - 15:30	250	4	4	6	50	5	0	0	20	0	0	0
15:30 - 15:45	400	9	5	8	65	7	0	0	28	0	0	0
15:45 - 16:00	554	12	6	10	84	8	0	0	38	0	0	0
16:00 - 16:15	712	13	6	11	107	12	0	0	45	0	0	0
16:15 - 16:30	888	17	7	12	135	15	0	0	52	0	1	0
16:30 - 16:45	1082	18	7	14	150	15	0	0	60	0	1	0
16:45 - 17:00	1344	19	7	14	171	15	0	0	75	0	1	0
17:00 - 17:15	1565	19	7	16	198	19	0	2	84	0	1	0
17:15 - 17:30	1787	21	9	18	219	24	0	2	90	0	1	0
17:30 - 17:45	1962	21	10	19	228	28	0	2	96	0	1	0
17:45 - 18:00	2096	23	11	20	233	28	0	2	99	0	1	0
18:00 - 18:15												



Projek Nr/Projek Name

Verkeerstelling/Traffic Count

Plek/Location:

Datum/Date:

Teller/Counter:

WITFONTEIN RD

WITFONTEIN RD

WITFONTEIN RD

Tyd	4				5				6			
	LIGHT	HEAVY	MBT	BUS	LIGHT	HEAVY	MBT	BUS	LIGHT	HEAVY	MBT	BUS
	05:45 - 06:00											
06:00 - 06:15	0	0	0	0	3	0	0	0	2	0	0	0
06:15 - 06:30	0	0	0	0	7	0	0	0	4	0	0	0
06:30 - 06:45	1	0	0	0	13	0	0	0	9	0	0	0
06:45 - 07:00	3	0	0	0	24	0	0	0	11	0	0	0
07:00 - 07:15	3	0	0	0	54	1	0	0	17	0	0	0
07:15 - 07:30	3	0	0	0	86	1	0	0	18	0	0	0
07:30 - 07:45	3	0	0	0	123	1	0	0	19	0	0	0
07:45 - 08:00	5	0	0	0	150	1	0	0	24	0	0	0
08:00 - 08:15	6	0	0	0	170	1	0	0	28	0	0	0
08:15 - 08:30	8	0	0	0	182	1	0	0	29	0	0	0
08:30 - 08:45	8	0	0	0	191	1	0	0	33	0	0	0
08:45 - 09:00	9	0	0	0	212	1	0	0	36	1	0	0
09:00 - 09:15												
14:45 - 15:00												
15:00 - 15:15	0	0	0	0	19	0	0	0	6	1	0	0
15:15 - 15:30	1	0	0	0	35	0	0	0	12	1	0	0
15:30 - 15:45	1	0	1	0	48	0	0	0	15	1	0	0
15:45 - 16:00	2	0	1	0	74	0	0	0	21	1	0	0
16:00 - 16:15	3	0	1	0	102	0	0	0	25	1	0	0
16:15 - 16:30	3	0	1	0	125	0	0	0	32	1	0	0
16:30 - 16:45	3	0	1	0	145	0	0	0	38	1	1	0
16:45 - 17:00	6	0	1	0	171	0	0	0	45	1	1	0
17:00 - 17:15	6	0	1	0	208	0	0	0	51	1	1	0
17:15 - 17:30	7	0	1	0	241	0	0	0	55	1	1	0
17:30 - 17:45	8	0	1	0	271	0	0	0	65	1	1	0
17:45 - 18:00	8	0	1	0	286	0	0	0	70	1	1	0
18:00 - 18:15												



Verkeerstelling/Traffic Count

Projek Nri/Projek Name _____

Plek/Location: _____

Datum/Date: _____

Teller/Counter: _____

N12

N12

N12

Tyd	7				8				9			
	LIGHT	HEAVY	MBT	BUS	LIGHT	HEAVY	MBT	BUS	LIGHT	HEAVY	MBT	BUS
05:45 - 06:00												
06:00 - 06:15	1	0	0	0	8	0	0	0	0	0	0	0
06:15 - 06:30	1	0	0	0	22	1	2	0	1	0	0	0
06:30 - 06:45	3	0	1	0	50	3	2	0	2	0	0	0
06:45 - 07:00	6	0	1	0	80	3	2	0	4	0	0	0
07:00 - 07:15	7	0	2	0	111	4	2	0	10	0	0	0
07:15 - 07:30	8	0	2	0	134	6	2	0	14	0	0	0
07:30 - 07:45	10	0	2	0	147	6	2	0	15	0	0	0
07:45 - 08:00	12	0	2	0	181	9	2	0	20	0	0	0
08:00 - 08:15	19	0	2	0	202	10	2	0	24	0	0	0
08:15 - 08:30	21	0	2	0	235	11	2	0	25	0	0	0
08:30 - 08:45	21	0	2	0	256	11	2	1	27	0	0	0
08:45 - 09:00	21	0	2	0	292	15	2	2	32	0	0	0
09:00 - 09:15												
14:45 - 15:00												
15:00 - 15:15	0	0	0	0	42	1	0	0	11	1	0	0
15:15 - 15:30	2	0	0	0	76	6	0	0	16	1	0	0
15:30 - 15:45	3	0	0	0	106	12	0	0	21	1	0	0
15:45 - 16:00	6	0	0	0	152	14	0	0	27	1	0	0
16:00 - 16:15	8	0	0	0	183	18	0	0	34	1	0	0
16:15 - 16:30	11	0	0	0	242	22	0	0	40	1	0	0
16:30 - 16:45	13	0	0	0	273	25	0	0	43	1	0	0
16:45 - 17:00	17	1	0	0	311	26	0	0	44	1	0	0
17:00 - 17:15	27	1	0	0	346	28	0	1	49	1	0	0
17:15 - 17:30	29	1	0	0	375	31	0	1	54	2	0	0
17:30 - 17:45	30	1	0	0	411	32	0	2	57	2	1	0
17:45 - 18:00	31	1	0	0	441	36	3	2	59	2	1	0
18:00 - 18:15												



Verkeerstelling/Traffic Count

Projek Nr/Projek Name _____

Plek/Location: _____

Datum/Date: _____

Teller/Counter: _____

WITFOONTEIN RD

WITFOONTEIN RD

WITFOONTEIN RD

Tyd	10				11				12			
	LIGHT	HEAVY	MBT	BUS	LIGHT	HEAVY	MBT	BUS	LIGHT	HEAVY	MBT	BUS
05:45 - 06:00												
06:00 - 06:15	0	0	1	0	5	0	0	0	23	0	2	2
06:15 - 06:30	0	0	1	0	9	0	0	0	69	0	4	5
06:30 - 06:45	3	0	1	0	28	0	0	0	199	1	6	6
06:45 - 07:00	5	0	1	0	96	0	0	0	469	1	8	9
07:00 - 07:15	7	0	1	0	200	0	0	0	665	2	9	10
07:15 - 07:30	7	0	1	0	261	0	0	0	831	4	11	13
07:30 - 07:45	7	0	1	0	295	0	0	0	1041	5	12	18
07:45 - 08:00	7	0	1	0	329	2	0	0	1241	6	16	19
08:00 - 08:15	10	0	1	0	345	2	0	0	1375	7	18	22
08:15 - 08:30	13	0	1	0	353	2	0	0	1487	7	23	24
08:30 - 08:45	23	0	1	0	368	2	0	0	1587	10	25	24
08:45 - 09:00	30	0	1	0	387	2	0	0	1723	11	26	25
09:00 - 09:15												
14:45 - 15:00												
15:00 - 15:15	7	1	0	0	8	0	0	0	141	2	0	0
15:15 - 15:30	12	1	0	0	16	0	0	0	248	3	3	3
15:30 - 15:45	14	1	0	0	37	0	1	0	375	4	6	3
15:45 - 16:00	19	1	0	0	60	0	1	0	508	6	11	5
16:00 - 16:15	24	1	0	0	70	0	1	0	647	10	14	5
16:15 - 16:30	25	1	0	0	81	0	1	0	784	13	17	6
16:30 - 16:45	30	1	1	0	102	0	1	0	935	13	20	7
16:45 - 17:00	41	1	1	0	119	0	1	0	1082	15	21	9
17:00 - 17:15	55	1	1	0	140	0	1	0	1213	15	21	9
17:15 - 17:30	61	1	1	0	151	0	1	0	1348	19	22	11
17:30 - 17:45	69	1	1	0	164	0	1	0	1384	23	26	13
17:45 - 18:00	72	2	2	0	175	0	1	0	1487	23	29	14
18:00 - 18:15												

Annexure C Detailed SIDRA Outputs

National Route 9 and Plantation Road

2022 AM Peak Hour

Movement Performance - Vehicles												
Mov ID	Turn	Demand Flows Total veh/h	HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: C J Langenhoven Road												
1	L2	1	3,0	0,069	5,6	LOS A	0,0	0,0	0,00	0,00	0,00	57,1
2	T1	139	3,0	0,069	0,0	LOS A	0,0	0,0	0,00	0,00	0,00	59,9
3	R2	1	3,0	0,001	5,9	LOS A	0,0	0,0	0,25	0,50	0,25	49,8
Approach		141	3,0	0,069	0,1	NA	0,0	0,0	0,00	0,01	0,00	59,9
East: Plantation Road												
4	L2	1	3,0	0,001	8,6	LOS A	0,0	0,0	0,24	0,83	0,24	48,8
5	T1	1	3,0	0,002	8,9	LOS A	0,0	0,1	0,36	0,80	0,36	41,0
6	R2	1	3,0	0,002	8,9	LOS A	0,0	0,1	0,36	0,80	0,36	48,5
Approach		3	3,0	0,002	8,8	LOS A	0,0	0,1	0,32	0,81	0,32	46,9
North: C J Langenhoven Road												
7	L2	1	3,0	0,067	5,6	LOS A	0,0	0,0	0,00	0,00	0,00	57,2
8	T1	135	3,0	0,067	0,0	LOS A	0,0	0,0	0,00	0,00	0,00	59,9
9	R2	1	3,0	0,001	5,8	LOS A	0,0	0,0	0,25	0,51	0,25	49,0
Approach		137	3,0	0,067	0,1	NA	0,0	0,0	0,00	0,01	0,00	59,9
West: Plantation Road												
10	L2	1	3,0	0,008	8,6	LOS A	0,0	0,2	0,34	0,83	0,34	48,0
11	T1	1	3,0	0,008	8,9	LOS A	0,0	0,2	0,34	0,83	0,34	40,8
12	R2	7	3,0	0,008	9,0	LOS A	0,0	0,2	0,34	0,83	0,34	47,8
Approach		9	3,0	0,008	8,9	LOS A	0,0	0,2	0,34	0,83	0,34	47,3
All Vehicles		291	3,0	0,069	0,5	NA	0,0	0,2	0,02	0,04	0,02	59,4

2022 PM Peak Hour

Movement Performance - Vehicles												
Mov ID	Turn	Demand Flows Total veh/h	HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: C J Langenhoven Road												
1	L2	7	3,0	0,103	5,6	LOS A	0,0	0,0	0,00	0,02	0,00	56,9
2	T1	202	3,0	0,103	0,0	LOS A	0,0	0,0	0,00	0,02	0,00	59,8
3	R2	3	3,0	0,002	6,0	LOS A	0,0	0,1	0,28	0,51	0,28	49,7
Approach		213	3,0	0,103	0,3	NA	0,0	0,1	0,00	0,03	0,00	59,6
East: Plantation Road												
4	L2	4	3,0	0,003	8,7	LOS A	0,0	0,1	0,28	0,83	0,28	48,8
5	T1	1	3,0	0,002	9,3	LOS A	0,0	0,1	0,43	0,78	0,43	40,6
6	R2	1	3,0	0,002	9,4	LOS A	0,0	0,1	0,43	0,78	0,43	48,3
Approach		6	3,0	0,003	8,9	LOS A	0,0	0,1	0,33	0,82	0,33	47,8
North: C J Langenhoven Road												
7	L2	1	3,0	0,082	5,6	LOS A	0,0	0,0	0,00	0,00	0,00	57,2
8	T1	166	3,0	0,082	0,0	LOS A	0,0	0,0	0,00	0,00	0,00	60,0
9	R2	1	3,0	0,001	6,0	LOS A	0,0	0,0	0,32	0,51	0,32	48,7
Approach		168	3,0	0,082	0,1	NA	0,0	0,0	0,00	0,01	0,00	59,9
West: Plantation Road												
10	L2	1	3,0	0,007	8,8	LOS A	0,0	0,2	0,41	0,82	0,41	47,7
11	T1	1	3,0	0,007	9,4	LOS A	0,0	0,2	0,41	0,82	0,41	40,4
12	R2	6	3,0	0,007	9,4	LOS A	0,0	0,2	0,41	0,82	0,41	47,5
Approach		8	3,0	0,007	9,3	LOS A	0,0	0,2	0,41	0,82	0,41	46,9
All Vehicles		396	3,0	0,103	0,5	NA	0,0	0,2	0,02	0,05	0,02	59,3

2027 AM Peak Hour

Movement Performance - Vehicles												
Mov ID	Turn	Demand Flows Total veh/h	HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: C J Langenhoven Road												
1	L2	24	3,0	0,092	5,6	LOS A	0,0	0,0	0,00	0,08	0,00	56,2
2	T1	162	3,0	0,092	0,0	LOS A	0,0	0,0	0,00	0,08	0,00	59,3
3	R2	2	3,0	0,001	5,9	LOS A	0,0	0,0	0,27	0,51	0,27	49,7
Approach		188	3,0	0,092	0,8	NA	0,0	0,0	0,00	0,08	0,00	58,9
East: Plantation Road												
4	L2	1	3,0	0,001	8,6	LOS A	0,0	0,0	0,27	0,82	0,27	48,8
5	T1	1	3,0	0,002	9,2	LOS A	0,0	0,1	0,40	0,79	0,40	40,8
6	R2	1	3,0	0,002	9,2	LOS A	0,0	0,1	0,40	0,79	0,40	48,4
Approach		3	3,0	0,002	9,0	LOS A	0,0	0,1	0,36	0,80	0,36	46,8
North: C J Langenhoven Road												
7	L2	1	3,0	0,078	5,6	LOS A	0,0	0,0	0,00	0,00	0,00	57,2
8	T1	157	3,0	0,078	0,0	LOS A	0,0	0,0	0,00	0,00	0,00	60,0
9	R2	2	3,0	0,001	6,0	LOS A	0,0	0,0	0,30	0,52	0,30	48,8
Approach		160	3,0	0,078	0,1	NA	0,0	0,0	0,00	0,01	0,00	59,8
West: Plantation Road												
10	L2	6	3,0	0,070	8,7	LOS A	0,3	2,2	0,40	0,87	0,40	47,7
11	T1	1	3,0	0,070	9,3	LOS A	0,3	2,2	0,40	0,87	0,40	40,4
12	R2	75	3,0	0,070	9,3	LOS A	0,3	2,2	0,40	0,87	0,40	47,5
Approach		82	3,0	0,070	9,3	LOS A	0,3	2,2	0,40	0,87	0,40	47,5
All Vehicles		434	3,0	0,092	2,2	NA	0,3	2,2	0,08	0,21	0,08	57,3

2027 PM Peak Hour

Movement Performance - Vehicles												
Mov ID	Turn	Demand Flows Total veh/h	HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: C J Langenhoven Road												
1	L2	69	3,0	0,152	5,6	LOS A	0,0	0,0	0,00	0,14	0,00	55,5
2	T1	235	3,0	0,152	0,0	LOS A	0,0	0,0	0,00	0,14	0,00	58,8
3	R2	4	3,0	0,002	6,1	LOS A	0,0	0,1	0,31	0,51	0,31	49,6
Approach		308	3,0	0,152	1,4	NA	0,0	0,1	0,00	0,14	0,00	58,1
East: Plantation Road												
4	L2	5	3,0	0,004	8,8	LOS A	0,0	0,1	0,30	0,83	0,30	48,8
5	T1	1	3,0	0,002	10,0	LOS B	0,0	0,1	0,48	0,78	0,48	40,1
6	R2	1	3,0	0,002	9,7	LOS A	0,0	0,1	0,48	0,78	0,48	47,9
Approach		7	3,0	0,004	9,1	LOS A	0,0	0,1	0,35	0,81	0,35	47,8
North: C J Langenhoven Road												
7	L2	1	3,0	0,096	5,6	LOS A	0,0	0,0	0,00	0,00	0,00	57,2
8	T1	194	3,0	0,096	0,0	LOS A	0,0	0,0	0,00	0,00	0,00	60,0
9	R2	6	3,0	0,004	6,4	LOS A	0,0	0,1	0,40	0,54	0,40	48,4
Approach		201	3,0	0,096	0,2	NA	0,0	0,1	0,01	0,02	0,01	59,6
West: Plantation Road												
10	L2	3	3,0	0,037	9,0	LOS A	0,2	1,1	0,47	0,86	0,47	47,3
11	T1	1	3,0	0,037	10,0	LOS A	0,2	1,1	0,47	0,86	0,47	39,8
12	R2	33	3,0	0,037	10,0	LOS B	0,2	1,1	0,47	0,86	0,47	47,1
Approach		37	3,0	0,037	9,9	LOS A	0,2	1,1	0,47	0,86	0,47	47,0
All Vehicles		554	3,0	0,152	1,6	NA	0,2	1,1	0,04	0,15	0,04	57,9

National Route 9 and Witfontein Road

2022 AM Peak Hour

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: C J Langenhoven Road												
1	L2	548	3,0	0,215	3,5	LOS A	1,1	7,7	0,09	0,44	0,09	54,0
2	T1	99	3,0	0,215	4,5	LOS A	1,1	7,7	0,33	0,48	0,33	54,7
3	R2	24	3,0	0,215	9,6	LOS A	1,1	7,7	0,33	0,48	0,33	49,2
Approach		672	3,0	0,215	3,9	LOS A	1,1	7,7	0,13	0,45	0,13	53,9
East: Witfontein Road												
4	L2	2	3,0	0,004	6,8	LOS A	0,0	0,1	0,60	0,60	0,60	49,4
5	T1	134	3,0	0,162	5,7	LOS A	0,7	5,4	0,62	0,72	0,62	43,3
6	R2	14	3,0	0,162	10,6	LOS B	0,7	5,4	0,62	0,72	0,62	48,0
Approach		149	3,0	0,162	6,2	LOS A	0,7	5,4	0,62	0,72	0,62	44,0
North: C J Langenhoven Road												
7	L2	7	3,0	0,076	7,3	LOS A	0,3	2,2	0,62	0,72	0,62	29,0
8	T1	113	3,0	0,097	6,7	LOS A	0,4	3,0	0,61	0,69	0,61	52,6
9	R2	17	3,0	0,097	11,6	LOS B	0,4	3,0	0,61	0,67	0,61	30,8
Approach		137	3,0	0,097	7,3	LOS A	0,4	3,0	0,61	0,69	0,61	49,1
West: Witfontein Road												
10	L2	2	3,0	0,411	4,6	LOS A	2,3	16,4	0,35	0,56	0,35	44,3
11	T1	247	3,0	0,411	4,6	LOS A	2,3	16,4	0,35	0,56	0,35	25,7
12	R2	837	3,0	0,449	9,7	LOS A	2,6	19,0	0,35	0,61	0,35	49,8
Approach		1086	3,0	0,449	8,5	LOS A	2,6	19,0	0,35	0,60	0,35	45,9
All Vehicles		2044	3,0	0,449	6,7	LOS A	2,6	19,0	0,31	0,56	0,31	48,7

2022 PM Peak Hour

Movement Performance - Vehicles												
Mov ID	Turn	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Queue Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: RoadName												
1	L2	958	3,0	0,346	3,6	LOS A	1,9	13,9	0,12	0,45	0,12	53,8
2	T1	98	3,0	0,346	4,5	LOS A	1,9	13,9	0,36	0,50	0,36	54,7
3	R2	40	3,0	0,346	9,7	LOS A	1,9	13,9	0,36	0,50	0,36	49,2
Approach		1096	3,0	0,346	3,9	LOS A	1,9	13,9	0,15	0,45	0,15	53,7
East: RoadName												
4	L2	4	3,0	0,007	6,1	LOS A	0,0	0,2	0,55	0,60	0,55	50,2
5	T1	122	3,0	0,147	5,0	LOS A	0,6	4,5	0,54	0,66	0,54	43,6
6	R2	25	3,0	0,147	9,9	LOS A	0,6	4,5	0,54	0,66	0,54	48,2
Approach		152	3,0	0,147	5,9	LOS A	0,6	4,5	0,54	0,65	0,54	45,0
North: RoadName												
7	L2	20	3,0	0,089	6,2	LOS A	0,3	2,5	0,53	0,62	0,53	29,4
8	T1	151	3,0	0,113	5,8	LOS A	0,5	3,3	0,52	0,60	0,52	53,3
9	R2	16	3,0	0,113	10,8	LOS B	0,5	3,3	0,52	0,59	0,52	31,3
Approach		186	3,0	0,113	6,3	LOS A	0,5	3,3	0,52	0,60	0,52	49,5
West: RoadName												
10	L2	39	3,0	0,283	4,6	LOS A	1,4	9,9	0,34	0,60	0,34	43,5
11	T1	74	3,0	0,283	4,6	LOS A	1,4	9,9	0,34	0,60	0,34	25,2
12	R2	611	3,0	0,310	9,7	LOS A	1,6	11,3	0,33	0,62	0,33	49,8
Approach		723	3,0	0,310	8,9	LOS A	1,6	11,3	0,33	0,62	0,33	47,8
All Vehicles		2157	3,0	0,346	5,9	LOS A	1,9	13,9	0,27	0,54	0,27	50,9

2027 AM Peak Hour

Movement Performance - Vehicles												
Mov ID	Turn	Demand Flows Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: RoadName												
1	L2	636	3,0	0,257	3,6	LOS A	1,3	9,6	0,09	0,44	0,09	53,9
2	T1	126	3,0	0,257	4,7	LOS A	1,3	9,6	0,39	0,51	0,39	54,3
3	R2	28	3,0	0,257	9,9	LOS A	1,3	9,6	0,39	0,51	0,39	48,8
Approach		791	3,0	0,257	4,0	LOS A	1,3	9,6	0,15	0,46	0,15	53,8
East: RoadName												
4	L2	3	3,0	0,006	7,8	LOS A	0,0	0,2	0,66	0,65	0,66	48,3
5	T1	156	3,0	0,215	6,7	LOS A	1,1	7,8	0,71	0,81	0,71	42,0
6	R2	17	3,0	0,215	11,5	LOS B	1,1	7,8	0,71	0,81	0,71	47,1
Approach		176	3,0	0,215	7,2	LOS A	1,1	7,8	0,71	0,81	0,71	42,9
North: RoadName												
7	L2	9	3,0	0,143	8,1	LOS A	0,6	4,4	0,69	0,80	0,69	28,7
8	T1	176	3,0	0,180	7,5	LOS A	0,9	6,1	0,69	0,77	0,69	51,9
9	R2	43	3,0	0,180	12,2	LOS B	0,9	6,1	0,69	0,76	0,69	30,3
Approach		228	3,0	0,180	8,4	LOS A	0,9	6,1	0,69	0,77	0,69	47,3
West: RoadName												
10	L2	15	3,0	0,495	4,9	LOS A	3,1	21,9	0,43	0,58	0,43	43,9
11	T1	287	3,0	0,495	4,9	LOS A	3,1	21,9	0,43	0,58	0,43	25,4
12	R2	971	3,0	0,541	10,0	LOS A	3,6	25,9	0,43	0,63	0,43	49,4
Approach		1273	3,0	0,541	8,8	LOS A	3,6	25,9	0,43	0,61	0,43	45,5
All Vehicles		2467	3,0	0,541	7,1	LOS A	3,6	25,9	0,39	0,59	0,39	48,3

2027 PM Peak Hour

Movement Performance - Vehicles												
Mov ID	Turn	Demand Flows Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate	Aver. No. Cycles	Average Speed km/h
South: RoadName												
1	L2	1111	3,0	0,420	3,6	LOS A	2,5	18,2	0,13	0,45	0,13	53,7
2	T1	154	3,0	0,420	4,8	LOS A	2,5	18,2	0,43	0,52	0,43	54,2
3	R2	47	3,0	0,420	10,0	LOS A	2,5	18,2	0,43	0,52	0,43	48,7
Approach		1312	3,0	0,420	4,0	LOS A	2,5	18,2	0,17	0,46	0,17	53,6
East: RoadName												
4	L2	5	3,0	0,009	6,7	LOS A	0,0	0,3	0,59	0,64	0,59	49,6
5	T1	142	3,0	0,184	5,5	LOS A	0,9	6,1	0,61	0,71	0,61	42,7
6	R2	29	3,0	0,184	10,4	LOS B	0,9	6,1	0,61	0,71	0,61	47,6
Approach		177	3,0	0,184	6,4	LOS A	0,9	6,1	0,61	0,71	0,61	44,1
North: RoadName												
7	L2	24	3,0	0,124	6,7	LOS A	0,5	3,7	0,59	0,67	0,59	29,1
8	T1	187	3,0	0,157	6,2	LOS A	0,7	5,0	0,59	0,65	0,59	52,8
9	R2	32	3,0	0,157	11,2	LOS B	0,7	5,0	0,58	0,64	0,58	30,9
Approach		243	3,0	0,157	6,9	LOS A	0,7	5,0	0,59	0,65	0,59	48,2
West: RoadName												
10	L2	66	3,0	0,356	5,0	LOS A	1,9	13,7	0,43	0,63	0,43	43,2
11	T1	86	3,0	0,356	5,0	LOS A	1,9	13,7	0,43	0,63	0,43	24,9
12	R2	708	3,0	0,389	10,1	LOS B	2,2	15,7	0,43	0,65	0,43	49,4
Approach		861	3,0	0,389	9,2	LOS A	2,2	15,7	0,43	0,65	0,43	47,3
All Vehicles		2593	3,0	0,420	6,2	LOS A	2,5	18,2	0,33	0,56	0,33	50,5